

britishceramictile

EC Declaration of Conformity



09

EN 14411 (Annex ZA)

I the undersigned, on behalf of the following manufacturer:

British Ceramic Tile Ltd
Heathfield, Newton Abbot, Devon, TQ12 6RF, United Kingdom
T: +44 (0)1626 834774, F: +44 (0)1626 834775, E: enquiries@britishceramictile.com

Declare that the following products:

Dry-pressed, glazed (GL) ceramic tile for internal floorings
Water absorption E > 10% Group BIII
EN 14411 (Annex L)

Meet the following Annex ZA requirements of EN 14411 Ceramic Tiles - Definitions, Classification, Characteristics and Marking:

Characteristics	Test Method	Declared Value
Reaction to fire	No testing	A1 _{fl} (see amended decision 96/603/EEC)
Release of dangerous substances - release of cadmium	BS EN ISO 10545-15	< 0.8 mg/dm ² (Statutory Instrument 2006 No. 1179. The Ceramic Articles in Contact with Food (England) Regulations 2006)
- release of lead	BS EN ISO 10545-15	< 0.07 mg/dm ² (Statutory Instrument 2006 No. 1179. The Ceramic Articles in Contact with Food (England) Regulations 2006)
Strength - breaking strength	BS EN ISO 10545-4	> 950 N
- modulus of rupture	BS EN ISO 10545-4	> 15 N/mm ²
Slipperiness	BS 7976	> 20 PTV

Independent Initial Type Testing (ITT) performed at the following notified laboratory: Ceram, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire ST4 7LQ, United Kingdom. ITT test reports are available upon request.

All products manufactured under an ISO 9001 Quality Management System certified by: CICS Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire ST4 7LQ, United Kingdom, a UKAS accredited certification body No. 006.

Mr Dick Sale
Production Director
24th August 2009

Dr Andrew McDermott
Technical Manager
24th August 2009